



LEDL

Design - Christoph Matthias & Veit Redl, 2012

Datenblatt

Artikelnummer:	06.01/06.03/06.04
Anwendung:	LED-Leuchte Innenleuchte Pendelleuchte
Schutzart:	IP20
Material:	Aluminium
Oberfläche:	eloxiert in schwarz, silber oder rot
Kabel sekundär:	Koaxial · 2x0,75 mm ² transparent
Pendellänge:	max. 2 m
Maße:	250 mm x 9 mm
LED-Betriebsgerät:	230 V ~ 50 Hz · 15 W · 350 mA Betriebsgerät in Baldachin
LED:	1 x max. 12 W · max. 350 mA LED-Lampe ist fest verbaut Austausch nur durch den Hersteller möglich. Energieklassen: A - A++
Farbtemperatur:	3000 K
Farbwiedergabeindex:	CRI > 90
Baldachin:	Montage auf Deckenauslass oder Unterputzdose möglich



Dimmbarkeit, Überlänge Pendel und Sonderfarben
auf Anfrage möglich

data sheet

article number:	06.01/06.03/06.04
application:	LED-light indoor light pendant light
protection class:	IP20
material:	aluminum
surface:	anodized black, silver or red
cable secondary:	coaxial · 2x0,75 mm ² transparent
pendulum length:	max. 2 m
dimensions:	250 mm x 9 mm
LED power supply unit:	230 V ~ 50 Hz · 15 W · 350 mA power supply unit in canopy
LED:	1 x max. 12 W · max. 350 mA contains built-in LED lamps The lamp can only be replaced by the manufacturer. Energy classes: A - A++
colour temperature:	3000 K
colour rendering index:	CRI > 90
canopy:	Mounting on ceiling outlet or flush-mounted box possible



dimmability, overlength pendulum and special colors
available on request